43

RoHS

23' 1/4" 3/4" 602 mm

82

SANREMO







SED VERSION

Guarantees an electronic dosing system through the button panel




SAP VERSION


Allows the semi-automatic programming of doses



Versions



SANREMO



17' 1/3" / 440 mm

31" / 780 mm 2 group SED/SAP

2 steam taps

1 water tap

1 one-cup filter hoder

2 two-cup filter hoders

3 group SED/SAP

2 steam taps

1 water tap

1 one-cup filter hoder

3 two-cup filter hoders

_Characteristics



ELECTRONIC AUTO-LEVEL

Through an electronic level probe the boiler is automatically filled and maintained to the right filling level.



ACTIVATED ELECTRONIC PRE-INFUSION

Management of the delayed activation of water solenoid in the first phase of brewing.



BOILER PRESSURE GAUGE

Allows to control the



PUMP PRESSURE GAUGE Allows to control the distribution pressure.

GROUP SR 61 Chromed brass grouphead with thermosiphonic circulation system optimized to maintain the ideal

coffee extraction temperature.



GROUP SR 61 Optimized to maintain the ideal coffee extraction temperature

EASY SERVICE

Fast access to the internal parts for quick and easy technical service.



AUTOMATIC CLEANING CYCLE Process to clean the



COMPETITION FILTERS

Exclusive Sanremo design, with shape and volume designed to capture the best coffee aromas and fragrances.



ENHANCED RESISTANCE



AD 880008

_Technical data		2 group	3 group
voltage	V	220-240 1N /	/ 380-415 3N
max input boiler/steam boiler's	kW	3.35 / 2.7	5.35 / 5.1
resistor power		5.1 / 4.5	
steam boiler capacity	lt	12	19
pump power	kW	0.15	0.15
net weight	lb / kg	139 / 63	196 / 89
gross weight (with shipping crate)	lb / kg	154 / 70	207 / 94



_Other

LED LIGHTING OF THE WORK AREA



CUP WARMER

Dedicated resistor to keep all the cups at the optimal temperature.



NAKED FILTER HODERS

